

Reg. No: 00139
Issue: 1
Doc. Date: 24.07.2008
English Version



SEQUESTON 6000

GENERAL DESCRIPTION

SEQUESTON 6000 is an excellent scale inhibitor to prevent the formation of calcium phosphate, calcium carbonate and other inorganic minerals. Sequeston 6000 can stabilize corrosion inhibitors such as zinc, phosphates and phosphonates; and it is compatible with any zinc or phosphate formula. Moreover, it can effectively to disperse inorganic micro-particles without pH influence.

Chemical Name : Acrylates-organic compounds mixture

SPECIFICATIONS

<u>Properties</u>	<u>Typical Values</u>
Appearance	Light amber liquid
Solid Content,%	42.0 - 44.0
pH, (1% water solution)	3.8 - 4.6
Density, g/cm ³	1.21 ±0.02

APPLICATIONS

SEQUESTON 6000 can be used as scale inhibitor for cooling water and boiler water system. The optimal chemical dosage is 10-30mg/L. When using with other chemicals' formula, the dosage should be determined by experiment.

PACKING

250kg per drum

TRANSPORT INFORMATION

UN No. 3265, Class 3, PG III

如需中文版产品介绍, 欢迎与我公司销售部连悉

The above information is, to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control.

Planet Chemicals Pte Ltd

5 Toh Guan Road East, Singapore 608831 Tel: +(65)-6872-6291 Fax: +(65)-6872 5655